Select sjSDM Staged-Tuning Survivors

Description

Deterministically ranks tier-pooled candidate evidence and returns the candidates allowed to enter the next tuning round. Candidates without complete converged evidence remain in the decision table but are pruned.

Usage

```
select_sjsdm_staged_survivors(
  data_candidate_aggregation = NULL,
  survivor_count = NULL,
  round_id = NULL
)
```

Arguments

`data_candidate_aggregation`	Candidate aggregation table containing 'candidate_id', 'normalized_loss_equal_id', and 'aggregation_status'.
`survivor_count`	Positive integer number of candidates to retain.
`round_id`	Positive integer tuning-round identifier.

Value

Tibble containing 'round_id', 'candidate_id', 'candidate_rank', 'normalized_loss_equal_id', and 'staged_decision' for every candidate. Eligible candidates are ordered first by loss and then candidate identifier. Ineligible candidates follow and always receive a 'prune' decision.

Examples

```
select_sjsdm_staged_survivors(
  data_candidate_aggregation = tibble::tibble(
    candidate_id = c("candidate_001", "candidate_002"),
    normalized_loss_equal_id = c(0.2, 0.3),
    aggregation_status = c("ok", "ok")
```

```
  ),
  survivor_count = 1L,
  round_id = 1L
)
```