Summarise sjSDM Model Provenance

Description

Combines cross-validation feasibility, selected regularization, and selected-fold diagnostics into one model-level provenance row.

Usage

```
summarise_sjsdm_model_provenance(
  data_feasibility = NULL,
  data_regularization = NULL,
  data_fold_diagnostics = NULL,
  fit_device = NULL,
  config_sjsdm_cv_fitting = NULL,
  config_model_fitting = NULL
)
```

Arguments

`data_feasibility`	One-row cross-validation feasibility table.
`data_regularization`	One-row selected regularization table returned by [resolve_sjsdm_regularization_for_fit()].
`data_fold_diagnostics`	Selected-candidate fold diagnostics. An empty data frame is allowed when held-out evaluation is unavailable.
`fit_device`	Scalar fitting-device identifier. Must be '"cpu"' or '"gpu"'.
`config_sjsdm_cv_fitting`, `config_model_fitting`	Validated cross-validation and final-model fitting configurations. Both are recorded explicitly so downstream audits can distinguish their budgets.

Value

One-row tibble containing model context, feasibility, data counts, fold-fit counts, effective MEV minimum/maximum/status and retained-taxon counts, and regularization source. It also records the fitting

device and versioned fold-local evaluation contract. The legacy scalar 'n_effective_mev' is retained when the count is constant across folds and is missing when counts vary.

Examples

```
## Not run:

summarise_sjsdm_model_provenance(

  data_feasibility = data_cross_validation_feasibility,

  data_regularization = model_regularization_for_fit,

  data_fold_diagnostics = data_sjsdm_out_of_fold_diagnostics,

  fit_device = "gpu"

)



## End(Not run)
```