

build_cross_validation_location_table.R

September 15, 2026

Contents

build_cross_validation_location_table	1
Index	3

build_cross_validation_location_table	
<i>Make Cross-Validation Location Table</i>	

Description

Collapses aligned model samples to unique sampling locations for location-level cross-validation. Complete paleo cores and modern plots are represented by one row each.

Usage

```
build_cross_validation_location_table(  
  data_sample_ids = NULL,  
  data_coords_projected = NULL,  
  location_column = "dataset_name"  
)
```

Arguments

data_sample_ids
Data frame with one row per aligned model sample and a location identifier column named by 'location_column'.

data_coords_projected
Data frame with one row per sampling location, location identifiers in row names, and finite 'coord_x_km' and 'coord_y_km' columns.

location_column
Character scalar naming the location identifier column in 'data_sample_ids'. Defaults to "dataset_name".

Details

Locations follow their first appearance in 'data_sample_ids'. Every sampled location must have exactly one projected coordinate row. Coordinate rows without aligned samples are omitted.

Value

Tibble with one row per sampled location and columns 'location_id', 'coord_x_km', 'coord_y_km', 'n_samples', and 'row_indices'. 'row_indices' is a list-column of integer row positions in 'data_sample_ids'.

Examples

```
data_sample_ids <-  
  tibble::tibble(dataset_name = c("core_a", "core_a", "core_b"))  
data_coords_projected <-  
  data.frame(  
    coord_x_km = c(10, 20),  
    coord_y_km = c(30, 40),  
    row.names = c("core_a", "core_b")  
  )  
build_cross_validation_location_table(  
  data_sample_ids = data_sample_ids,  
  data_coords_projected = data_coords_projected  
)
```

Index

build_cross_validation_location_table,
[1](#)