

build_sjsdm_candidate_fold_result.R

September 15, 2026

Contents

build_sjsdm_candidate_fold_result 1

Index 3

build_sjsdm_candidate_fold_result
Build One sjSDM Candidate-Fold Result

Description

Constructs one typed tuning row and its compact prediction-cache record for a completed or failed candidate lifecycle.

Usage

```
build_sjsdm_candidate_fold_result(  
  data_candidate = NULL,  
  list_fold_context = NULL,  
  fit_seed = NA_integer_,  
  score_seed = NA_integer_,  
  fit_status = NULL,  
  error_message = NA_character_,  
  data_metrics = NULL,  
  data_predicted = NULL,  
  fit_seconds = NA_real_,  
  prediction_seconds = NA_real_,  
  scoring_seconds = NA_real_,  
  data_fit_attempts = tibble::tibble(),  
  converged = NA,  
  actual_n_iter = NA_integer_,  
  actual_n_sampling = NA_integer_,  
  epochs_run = NA_integer_,  
  linear_trend_slope = NA_real_,  
  median_diff = NA_real_,  
  early_stopping_triggered = NA  
)
```

Arguments

`data_candidate` One-row candidate table with the candidate identifier and six parameters.

`list_fold_context`
Fold context containing identifiers, sizes, and the CV strategy.

`fit_seed, score_seed`
Derived candidate seeds, or typed missing integers before candidate work.

`fit_status` One of 'preparation_error', 'fit_error', 'convergence_error', 'non_converged', 'prediction_error', 'scoring_error', or 'ok'.

`error_message` Character failure message, or a missing character value for success.

`data_metrics` Optional named list of the five candidate scoring metrics.

`data_predicted` Optional held-out probability matrix. Fitted model objects are never stored.

`fit_seconds, prediction_seconds, scoring_seconds`
Candidate lifecycle timings in seconds.

`data_fit_attempts`
Attempt-level CV fitting provenance, or an empty table.

`converged, actual_n_iter, actual_n_sampling, epochs_run`
Final-attempt convergence and actual-budget fields.

`linear_trend_slope, median_diff, early_stopping_triggered`
Final-attempt convergence diagnostics.

Value

Named list containing one-row 'data_tuning' and 'list_prediction'.

Index

`build_sjsdm_candidate_fold_result`, [1](#)