

evaluate_sjsdm_candidate_guardrails.R

September 15, 2026

Contents

evaluate_sjsdm_candidate_guardrails 1

Index 3

evaluate_sjsdm_candidate_guardrails
Assess sjSDM Candidate Guardrails

Description

Compares a tuning candidate with its reference across tuning repeats and an independent fold-local refit.

Usage

```
evaluate_sjsdm_candidate_guardrails(  
  data_tuning_summary = NULL,  
  data_candidate_repeat_metrics = NULL,  
  data_reference_repeat_metrics = NULL,  
  candidate_id = NULL,  
  reference_candidate_id = NULL,  
  maximum_discrimination_decrease = 0.01,  
  minimum_tjur_r2 = 0.1  
)
```

Arguments

`data_tuning_summary` Repeat-by-candidate tuning summary.

`data_candidate_repeat_metrics` Candidate repeat metrics from [summarise_sjsdm_fold_metrics()].

`data_reference_repeat_metrics` Reference repeat metrics with the same schema as the candidate metrics.

`candidate_id` Candidate identifier to assess.

`reference_candidate_id` Reference identifier used for comparison.

`maximum_discrimination_decrease`

Largest allowed repeat-level decrease in AUC or Tjur R2. Defaults to '0.01'.

`minimum_tjur_r2`

Minimum candidate mean fold-macro Tjur R2. Defaults to '0.1'.

Details

Acceptance requires lower tuning NLL in every repeat, tuning AUC within the discrimination tolerance, non-inferior independent-refit AUC, Tjur R2, log loss, and Brier score in every repeat, and the scientific Tjur R2 gate.

Value

A named list containing tuning-repeat comparisons, independent-refit comparisons, and a one-row guardrail summary.

Examples

```
## Not run:
evaluate_sjsdm_candidate_guardrails(
  data_tuning_summary = data_tuning,
  data_candidate_repeat_metrics = data_candidate_metrics,
  data_reference_repeat_metrics = data_reference_metrics,
  candidate_id = "candidate_002",
  reference_candidate_id = "candidate_001"
)

## End(Not run)
```

Index

`evaluate_sjsdm_candidate_guardrails`, [1](#)