

# load\_sjsdm\_tier\_tuning\_artifact.R

September 15, 2026

## Contents

|                                           |          |
|-------------------------------------------|----------|
| load_sjsdm_tier_tuning_artifact . . . . . | 1        |
| <b>Index</b>                              | <b>3</b> |

---

|                                        |
|----------------------------------------|
| load_sjsdm_tier_tuning_artifact        |
| <i>Read sjSDM Tier Tuning Artifact</i> |

---

## Description

Reads the shared tier artifact table and selects the row matching one unit model context.

## Usage

```
load_sjsdm_tier_tuning_artifact(  
  store_path = NULL,  
  data_model_context = NULL,  
  read_target_function = targets::tar_read_raw  
)
```

## Arguments

|                      |                                                                   |
|----------------------|-------------------------------------------------------------------|
| store_path           | Character scalar path to the dedicated tier-tuning targets store. |
| data_model_context   | One-row model-context table.                                      |
| read_target_function | Injectable target reader. Defaults to [targets::tar_read_raw()].  |

## Value

One matching artifact row, or an exact typed-empty table when the shared target is unavailable or does not yet contain the requested context.

**Examples**

```
## Not run:
load_sjsdm_tier_tuning_artifact(
  store_path = "Data/targets/paleo/pipeline_sjsdm_tier_tuning",
  data_model_context = data_sjsdm_model_context
)

## End(Not run)
```

# Index

`load_sjsdm_tier_tuning_artifact`, [1](#)