

# resolve\_scale\_id\_from\_store.R

September 15, 2026

## Contents

resolve\_scale\_id\_from\_store . . . . . 1

**Index** 3

---

resolve\_scale\_id\_from\_store  
*Get Scale ID from Current Targets Store Path*

---

## Description

Determines whether the currently active targets store corresponds to a spatial unit by inspecting the store path and checking it against the project's spatial grid CSV catalogue. Returns the 'scale\_id' string for spatial pipelines, or 'NULL' for non-spatial (named-project) pipelines.

## Usage

```
resolve_scale_id_from_store(  
  store = targets::tar_path_store(),  
  file = here::here("Data/Input/spatial_grid.csv")  
)
```

## Arguments

|       |                                                                                                                                                                                                                                   |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| store | A single character string giving the path to the targets data store. Default: 'targets::tar_path_store()', which resolves correctly both inside target commands (including callr worker processes) and when called interactively. |
| file  | Path to the spatial grid CSV catalogue file. Default: 'here::here("Data/Input/spatial_grid.csv")'.                                                                                                                                |

## Details

The store path convention for spatial pipelines is: 'target\_store/scale\_id/pipeline\_name/'. The function extracts the second-to-last path component via 'basename(dirname(store))' and checks whether it appears in the 'scale\_id' column of the spatial grid CSV. For non-spatial pipelines (e.g. 'Data/targets/cz\_paleo/pipeline\_paleo\_core/') the candidate ("project\_cz\_paleo") is not in the CSV, so 'NULL' is returned. When the CSV file does not exist the function returns 'NULL' gracefully.

**Value**

A single character string with the 'scale\_id' when the store path corresponds to a spatial unit in the CSV catalogue, or 'NULL' otherwise.

**See Also**

load\_spatial\_window, load\_model\_tuning\_parameters

# Index

`resolve_scale_id_from_store`, [1](#)