

run_main_analysis_stage.R

September 15, 2026

Contents

run_main_analysis_stage 1

Index 3

run_main_analysis_stage
Run a Main Analysis Stage

Description

Runs an ordered table of main-analysis component scripts in isolated R subprocesses, streams their output into live logs, and records statuses.

Usage

```
run_main_analysis_stage(  
  stage_id = NULL,  
  data_components = NULL,  
  run_id = NULL,  
  continue_on_error = FALSE,  
  next_stage_script = NULL,  
  runner_function = processx::run,  
  log_root = here::here("Data", "Temp", "Main_analysis_execution"),  
  verbose = TRUE  
)
```

Arguments

stage_id	Non-empty identifier for the numbered main-analysis stage.
data_components	Data frame with unique 'component_id' and 'script_path' columns. Optional list-columns 'arguments' and 'environment' supply subprocess arguments and environment variables.
run_id	Non-empty identifier shared by all component batches in one stage run.

<code>continue_on_error</code>	Logical scalar. If 'TRUE', all independent components are attempted before the stage fails. If 'FALSE', execution stops after the first failure.
<code>next_stage_script</code>	Optional project-relative path printed after a successful stage.
<code>runner_function</code>	Injectable subprocess runner. Defaults to <code>[processx::run()]</code> .
<code>log_root</code>	Directory under which stage logs and status CSV files are written.
<code>verbose</code>	Logical. If 'TRUE' (default), progress messages are printed to the console.

Value

Tibble with one row per attempted component and its exit status and log.

Index

`run_main_analysis_stage`, [1](#)