

run_sjsdm_cv_calibration_benchmark.R

September 23, 2026

Contents

run_sjsdm_cv_calibration_benchmark	1
--	---

Index	3
--------------	----------

run_sjsdm_cv_calibration_benchmark	
<i>Run an Adaptive sjSDM CV Budget Calibration</i>	

Description

Screens all candidates on three folds at a reduced sampling budget. After each stable adjacent-rung pair, it confirms the winner and runner-up on all five folds of repeats one and two at the production sampling budget.

Usage

```
run_sjsdm_cv_calibration_benchmark(  
  data_candidates = NULL,  
  list_prepared_folds = NULL,  
  sel_abiotic_formula = NULL,  
  config_sjsdm_cv_fitting = NULL,  
  data_ladder = build_sjsdm_cv_calibration_ladder(),  
  screening_fold_ids = 1:3,  
  confirmation_fold_ids = 1:5,  
  confirmation_sampling = 200L,  
  n_confirmation_candidates = 2L,  
  repeat_confirmation_loss_tolerance = 0.02,  
  checkpoint_file = NULL,  
  rung_function = run_sjsdm_cv_calibration_rung,  
  verbose = TRUE,  
  ...  
)
```

Arguments

<code>data_candidates</code> , <code>list_prepared_folds</code> , <code>sel_abiotic_formula</code>	Calibration model inputs.
<code>config_sjsdm_cv_fitting</code>	Validated structural CV fitting configuration.
<code>data_ladder</code>	Ordered budget ladder from <code>[build_sjsdm_cv_calibration_ladder()]</code> .
<code>screening_fold_ids</code> , <code>confirmation_fold_ids</code>	Deterministic fold IDs used for screening and confirmation.
<code>confirmation_sampling</code>	Production sampling budget used for confirmation.
<code>n_confirmation_candidates</code>	Number of leading screening candidates retained for confirmation.
<code>repeat_confirmation_loss_tolerance</code>	Maximum relative loss gap allowed above the repeat-two winner.
<code>checkpoint_file</code>	Optional <code>‘.qs’</code> path used to resume completed runs after interruption.
<code>rung_function</code>	Injectable rung executor for deterministic orchestration tests.
<code>verbose</code>	Logical. If <code>‘TRUE’</code> , progress is printed to the console.
<code>...</code>	Additional arguments passed to <code>[run_sjsdm_cv_calibration_rung()]</code> .

Value

Calibration status, accepted budget when available, benchmark evidence, and attempt-level provenance accumulated before stopping.

Index

`run_sjsdm_cv_calibration_benchmark`, [1](#)