

scale_spatial_for_fit.R

September 15, 2026

Contents

scale_spatial_for_fit	1
Index	2

scale_spatial_for_fit	<i>Scale Spatial Predictors for Model Fitting</i>
-----------------------	---

Description

Centres and scales all spatial predictor columns, records the scaling attributes for later back-transformation, and returns both the scaled data frame and the attributes as a named list.

Usage

```
scale_spatial_for_fit(data_spatial = NULL)
```

Arguments

<code>data_spatial</code>	A data frame with row names in the format " <code><dataset_name>__<age></code> " and numeric columns containing spatial predictor variables (e.g. <code>'coord_x_km'</code> , <code>'coord_y_km'</code>), as returned by <code>'prepare_spatial_predictors_for_fit()'</code> .
---------------------------	---

Details

All columns are centred (mean subtracted) and divided by their standard deviation using `'base::scale()'`, provided more than one sample is present. When only one row exists, only centring is applied.

Value

A named list with two elements:

'data_spatial_scaled' A data frame with the same row names as the input, with all predictor columns centred and scaled. When only one sample is present, columns are centred only (`scale = FALSE`).

'spatial_scale_attributes' A named list of `'center'` and `'scale'` attributes for each predictor column, which can be used to back-transform predictions.

See Also

[prepare_spatial_predictors_for_fit()], [build_jsdm_fit_input()]

Index

`scale_spatial_for_fit`, [1](#)