

select_sjsdm_staged_survivors.R

September 15, 2026

Contents

select_sjsdm_staged_survivors	1
Index	3

select_sjsdm_staged_survivors
<i>Select sjSDM Staged-Tuning Survivors</i>

Description

Deterministically ranks complete tier-pooled candidate evidence and returns the candidates allowed to enter the next tuning round.

Usage

```
select_sjsdm_staged_survivors(  
  data_candidate_aggregation = NULL,  
  survivor_count = NULL,  
  round_id = NULL  
)
```

Arguments

data_candidate_aggregation	Candidate aggregation table containing 'candidate_id', 'normalized_loss_equal_id', and 'aggregation_status'.
survivor_count	Positive integer number of candidates to retain.
round_id	Positive integer tuning-round identifier.

Value

Tibble containing 'round_id', 'candidate_id', 'candidate_rank', 'normalized_loss_equal_id', and 'staged_decision' for every candidate. Candidates are ordered by loss and then candidate identifier.

Examples

```
select_sjsdm_staged_survivors(  
  data_candidate_aggregation = tibble::tibble(  
    candidate_id = c("candidate_001", "candidate_002"),  
    normalized_loss_equal_id = c(0.2, 0.3),  
    aggregation_status = c("ok", "ok")  
  ),  
  survivor_count = 1L,  
  round_id = 1L  
)
```

Index

`select_sjsdm_staged_survivors`, [1](#)