

aggregate_sjsdm_tuning_by_tier.R

August 11, 2026

Contents

aggregate_sjsdm_tuning_by_tier	1
Index	3

aggregate_sjsdm_tuning_by_tier
<i>Aggregate sjSDM Tuning by Tier</i>

Description

Aggregates normalized candidate loss within source IDs and then across a compatible spatial tier using equal source-ID weighting.

Usage

```
aggregate_sjsdm_tuning_by_tier(  
  data_tuning_summary = NULL,  
  include_sample_weighted = TRUE  
)
```

Arguments

data_tuning_summary	Repeat-level tuning summaries from [summarise_sjsdm_tuning_candidates()] with source and model-context columns.
include_sample_weighted	Logical scalar. When true, also reports a sensitivity selection weighted by the number of observed response values contributed by each source ID.

Details

Input rows must describe one tier, taxonomic resolution, response family, predictor structure, and candidate-table hash. Every source ID must provide the same candidate identifiers and parameter values. Candidates with an incomplete result for any source ID remain visible but are not selectable.

Value

Named list with `source_candidate_loss`, `candidate_aggregation`, and `selection_sensitivity` tibbles. The primary selection always uses equal source-ID weighting.

Examples

```
## Not run:  
aggregate_sjsdm_tuning_by_tier(  
  data_tuning_summary = data_tuning_summary  
)  
  
## End(Not run)
```

Index

`aggregate_sjsdm_tuning_by_tier`, [1](#)