

build_cross_validation_grid_candidates_from_resolution

August 11, 2026

Contents

build_cross_validation_grid_candidates_from_resolution	1
Index	3

build_cross_validation_grid_candidates_from_resolution
<i>Make Cross-Validation Grid Candidates From Fold Resolution</i>

Description

Derives spatial-grid candidates only for spatially stratified grouped cross-validation.

Usage

```
build_cross_validation_grid_candidates_from_resolution(  
  data_locations = NULL,  
  data_fold_resolution = NULL,  
  target_locations_per_cell = 5,  
  grid_size_multipliers = 2^base::seq(-2, 2)  
)
```

Arguments

`data_locations` Location table returned by [build_cross_validation_location_table()].

`data_fold_resolution` One-row table returned by [resolve_cross_validation_fold_count()].

`target_locations_per_cell, grid_size_multipliers` Arguments passed to [build_cross_validation_grid_candidates()].

Value

Grid-candidate tibble. Gridless strategies return a zero-row tibble with the stable candidate schema.

Examples

```
data_locations <-  
  tibble::tibble(  
    location_id = base::letters[1:6],  
    coord_x_km = base::seq_len(6L),  
    coord_y_km = base::seq_len(6L),  
    n_samples = base::rep(1L, 6L),  
    row_indices = base::as.list(base::seq_len(6L))  
  )  
data_resolution <-  
  resolve_cross_validation_fold_count(6L, 5L)  
build_cross_validation_grid_candidates_from_resolution(  
  data_locations = data_locations,  
  data_fold_resolution = data_resolution  
)
```

Index

`build_cross_validation_grid_candidates_from_resolution,`
[1](#)