

build_sjsdm_cached_selected_folds.R

August 11, 2026

Contents

build_sjsdm_cached_selected_folds 1

Index 3

build_sjsdm_cached_selected_folds
Build Cached Selected sjSDM Folds

Description

Reconstructs the established selected-candidate OOF prediction and diagnostic artifacts from tuning-time probabilities without fitting the selected candidate again.

Usage

```
build_sjsdm_cached_selected_folds(  
  data_assignments = NULL,  
  data_selected_candidate = NULL,  
  data_sample_ids = NULL,  
  taxon_names = NULL,  
  list_prediction_cache = NULL  
)
```

Arguments

data_assignments, data_selected_candidate, data_sample_ids,
taxon_names
Inputs accepted by [run_sjsdm_selected_candidate_folds()].

list_prediction_cache
Fold caches returned by [run_sjsdm_tuning_candidates()] when 'retain_prediction_cache = TRUE'.

Value

Named list with the unchanged 'data_predictions' and 'data_diagnostics' public schemas. Diagnostic fit seeds identify the tuning fits that produced the reused probabilities.

Examples

```
## Not run:
build_sjsdm_cached_selected_folds(
  data_assignments = data_assignments,
  data_selected_candidate = data_selected_candidate,
  data_sample_ids = data_sample_ids,
  taxon_names = taxon_names,
  list_prediction_cache = list_prediction_cache
)

## End(Not run)
```

Index

`build_sjsdm_cached_selected_folds`, [1](#)