

load_trait_domain_names_from_vegvault.R

August 11, 2026

Contents

load_trait_domain_names_from_vegvault	1
Index	3

load_trait_domain_names_from_vegvault
<i>Load Trait Domain Names from VegVault</i>

Description

Loads all unique trait domain names from the 'TraitsDomain' table.

Usage

```
load_trait_domain_names_from_vegvault(  
  path_vegvault = here::here("Data/Input/VegVault.sqlite"),  
  verbose = TRUE  
)
```

Arguments

path_vegvault	A character string specifying the path to the VegVault SQLite database (default: 'here::here("Data/Input/VegVault.sqlite")').
verbose	Logical. If 'TRUE' (default), progress messages are printed to the console via 'cli'. Set to 'FALSE' to suppress all console output.

Details

The function performs the following steps:

1. Validates input parameters.
2. Checks the presence of the VegVault SQLite database using 'validate_vegvault_presence()'.
3. Opens a DBI connection to the SQLite database.
4. Queries the 'TraitsDomain' table for distinct 'trait_domain_name' values and collects results.
5. Closes the database connection.
6. Removes 'NA' values from the result.
7. Asserts that at least one domain name was found.
8. Optionally logs the result via 'cli::cli_inform()'.
9. Returns the character vector of domain names.

Value

A character vector of unique, non-‘NA’ trait domain names found in the ‘TraitsDomain’ table.

See Also

[load_trait_records_from_vegvault()]

Index

load_trait_domain_names_from_vegvault,
[1](#)