

run_sjsdm_tuning_sequence.R

August 11, 2026

Contents

run_sjsdm_tuning_sequence	1
Index	3

run_sjsdm_tuning_sequence	
	<i>Run the Shared sjSDM Tuning Sequence</i>

Description

Orchestrates isolated unit and tier stores for exhaustive or staged tuning. Staged execution alternates one cumulative unit round with one tier-wide survivor target, then publishes the existing final tier artifact.

Usage

```
run_sjsdm_tuning_sequence(  
  unit_pipeline = NULL,  
  tuning_target_names = NULL,  
  unit_store_suffixes = NULL,  
  prebuild_interpolation = FALSE,  
  fresh_run = FALSE,  
  tuning_strategy = NULL,  
  n_rounds = NULL,  
  run_pipeline_function = run_pipeline,  
  vec_allowed_profile_roles = base::c("main", "smoke"),  
  vec_allowed_profile_statuses = "active",  
  has_tuning_evidence_function = has_sjsdm_tuning_evidence,  
  target_store = load_active_config_value("target_store")  
)
```

Arguments

`unit_pipeline` Character scalar path to the unit pipeline script.

`tuning_target_names` Non-empty character vector of public unit tuning-summary targets.

<code>unit_store_suffixes</code>	Optional character vector of isolated spatial-unit store suffixes. ‘NULL’ runs one non-nested unit store, as used by temporal mapped pipelines.
<code>prebuild_interpolation</code>	Logical forwarded to <code>[run_pipeline()]</code> for unit executions.
<code>fresh_run</code>	Logical. When true, destroys unit stores on their first round and the tier store before its first aggregation. Later rounds always resume.
<code>tuning_strategy</code>	Character scalar, “exhaustive” or “staged”.
<code>n_rounds</code>	Positive integer configured repeat/tuning-round count.
<code>run_pipeline_function</code>	Injectable pipeline runner. Defaults to <code>[run_pipeline()]</code> .
<code>vec_allowed_profile_roles</code>	Profile roles forwarded to <code>[run_pipeline()]</code> . Production callers should retain ‘c("main", "smoke")’; dedicated runners authorize other roles.
<code>vec_allowed_profile_statuses</code>	Profile statuses forwarded to <code>[run_pipeline()]</code> . Production callers should retain “active”.
<code>has_tuning_evidence_function</code>	Injectable fail-closed evidence checker. Defaults to <code>[has_sjsdm_tuning_evidence()]</code> .
<code>target_store</code>	Root targets-store path. Defaults to the active configuration value.

Value

Invisible ‘NULL’. Pipeline stores contain the durable results.

Index

run_sjsdm_tuning_sequence, [1](#)