

validate_sample_count.R

August 6, 2026

Contents

validate_sample_count 1

Index 3

validate_sample_count *Validate Sample Count*

Description

Guards against running downstream data preparation and model fitting on a time slice with too few '(dataset_name, age)' combinations. Returns 'data_sample_ids' unchanged when the row count is at least 'minimum_sample_count'. Stops with an informative error when the count falls below the threshold, preventing expensive model fitting on near-empty slices.

Usage

```
validate_sample_count(data_sample_ids = NULL, minimum_sample_count = 1)
```

Arguments

data_sample_ids
A data frame with at least the columns 'dataset_name' and 'age', as returned by 'align_sample_ids()'. Each row represents one valid '(dataset_name, age)' pair.

minimum_sample_count
A single positive integer giving the minimum number of samples (rows) required to proceed with data preparation and model fitting. Default is 1.

Details

The check counts 'nrow(data_sample_ids)' after the time-slice filter has been applied by 'align_sample_ids(subset_age = ...)'. If the count falls below 'minimum_sample_count', 'cli::cli_abort()' is called with a message that reports the actual sample count and the threshold, allowing the user to adjust the configuration or the input data. This check is intended to be placed in the per-slice pipeline (e.g. 'pipe_segment_sample_filter_age') so that slices without sufficient data fail immediately, before any expensive preparation or model fitting.

Value

The input 'data_sample_ids' unchanged, when 'nrow(data_sample_ids) >= minimum_sample_count'.

See Also

[align_sample_ids()], [validate_community_taxon_count()]

Index

`validate_sample_count`, [1](#)