

build_base_terminal_plot.R

June 18, 2026

Contents

build_base_terminal_plot	1
Index	3

build_base_terminal_plot
<i>Create an ORACLE terminal base plot</i>

Description

Creates the reusable dark CRT terminal scaffold used by IAVS 2026 story and atmospheric figures.

Usage

```
build_base_terminal_plot(  
  title,  
  prompt,  
  plot_dimensions = c(x_min = 0, x_max = 100, y_min = 0, y_max = 100 * (9/16)),  
  boundary_buffer = 2,  
  width = 1600,  
  height = 900,  
  units = "px",  
  dpi = 300,  
  palette = NULL,  
  background_colour = NULL,  
  terminal_label = ">ORACLE//",  
  noise_points = 900L,  
  scanline_spacing = 1.25  
)
```

Arguments

title	Character scalar. Terminal heading shown at the top left.
prompt	Character scalar. Prompt or status text shown below the heading.
plot_dimensions	Named numeric vector with 'x_min', 'x_max', 'y_min', and 'y_max'. These values define the coordinate system for all subsequent layers.

<code>boundary_buffer</code>	Numeric scalar. Internal margin used for the terminal border and text.
<code>width</code>	Numeric scalar. Output canvas width passed to <code>'ggview::canvas()'</code> .
<code>height</code>	Numeric scalar. Output canvas height passed to <code>'ggview::canvas()'</code> .
<code>units</code>	Character scalar. Canvas units passed to <code>'ggview::canvas()'</code> .
<code>dpi</code>	Numeric scalar. Canvas resolution passed to <code>'ggview::canvas()'</code> .
<code>palette</code>	Optional named character vector of ORACLE colours. If <code>'NULL'</code> , colours are read with <code>'get_oracle_palette_values()'</code> .
<code>background_colour</code>	Optional background colour. If <code>'NULL'</code> , <code>'palette[["background"]]'</code> is used.
<code>terminal_label</code>	Character scalar. Footer label shown in amber at the lower left.
<code>noise_points</code>	Integer scalar. Number of faint CRT noise points to draw.
<code>scanline_spacing</code>	Numeric scalar. Vertical spacing between scanlines.

Details

This function intentionally keeps `scanline`, `CRT-noise`, `canvas`, and `blank-theme` helpers internal so presentation scripts can reuse one stable public entry point.

Value

A `'ggplot'` object with a configured terminal canvas.

See Also

`add_panel`, `get_oracle_palette_values`, `create_oracle_theme`

Index

`build_base_terminal_plot`, [1](#)