

aggregate_jsdm_variance_components.R

August 16, 2026

Contents

aggregate_jsdm_variance_components	1
Index	3

aggregate_jsdm_variance_components
<i>Aggregate sjSDM Variance Components Across Time Slices</i>

Description

Extracts variance partitioning fractions from a named list of sjSDM ANOVA objects and assembles a long-format tibble with one row per age and component combination.

Usage

```
aggregate_jsdm_variance_components(list_model_anova)
```

Arguments

list_model_anova
A named list of sjSDManova objects, one per time slice. Names must end with a numeric age value (e.g. "timeslice_500"). 'NULL' entries and objects without a named "results" element are silently discarded.

Details

The age is parsed from the trailing digit sequence in each list-element name. Fraction extraction and negative-value clamping are delegated to [extract_jsdm_variance_fractions()].

Value

A tibble with columns:

age Numeric age (cal yr BP) extracted from the list-element name.

component Character. Human-readable component label (e.g. "Abiotic", "Associations", "Spatial").

R2_Nagelkerke Numeric. Nagelkerke RB2 for the component, clamped to [0, Inf).

See Also

[[compute_jsdm_variance_partition\(\)](#)], [[extract_jsdm_variance_fractions\(\)](#)]

Index

`aggregate_jsdm_variance_components`, [1](#)