

# build\_cross\_validation\_assignments\_from\_resolution.R

August 16, 2026

## Contents

|                                                              |          |
|--------------------------------------------------------------|----------|
| build_cross_validation_assignments_from_resolution . . . . . | 1        |
| <b>Index</b>                                                 | <b>3</b> |

---

|                                                               |
|---------------------------------------------------------------|
| build_cross_validation_assignments_from_resolution            |
| <i>Make Cross-Validation Assignments From Fold Resolution</i> |

---

## Description

Dispatches a resolved cross-validation strategy to spatially stratified or leave-one-location-out assignment while preserving one assignment schema.

## Usage

```
build_cross_validation_assignments_from_resolution(  
  data_locations = NULL,  
  data_fold_resolution = NULL,  
  data_grid_calibration = NULL,  
  n_repeats = 1L,  
  seed = 900723L,  
  assignment_source = "per_id"  
)
```

## Arguments

|                       |                                                                                  |
|-----------------------|----------------------------------------------------------------------------------|
| data_locations        | Location table returned by [build_cross_validation_location_table()].            |
| data_fold_resolution  | One-row table returned by [resolve_cross_validation_fold_count()].               |
| data_grid_calibration | Table returned by [compute_cross_validation_grid_calibration_from_resolution()]. |
| n_repeats             | Positive integer number of deterministic spatial assignment repeats.             |
| seed                  | Non-negative integer assignment seed.                                            |
| assignment_source     | Non-empty character scalar recording assignment provenance.                      |

**Value**

Tibble with the shared assignment columns plus 'cv\_strategy' and 'assignment\_source'. A no-holdout resolution returns a zero-row tibble with the same schema.

**Examples**

```
data_locations <-  
  tibble::tibble(  
    location_id = base::letters[1:6],  
    coord_x_km = base::seq_len(6L),  
    coord_y_km = base::seq_len(6L),  
    n_samples = base::rep(1L, 6L),  
    row_indices = base::as.list(base::seq_len(6L))  
  )  
data_resolution <-  
  resolve_cross_validation_fold_count(6L, 5L)  
build_cross_validation_assignments_from_resolution(  
  data_locations = data_locations,  
  data_fold_resolution = data_resolution,  
  data_grid_calibration = tibble::tibble()  
)
```

# Index

build\_cross\_validation\_assignments\_from\_resolution,  
1