

# compute\_sjsdm\_decomposition\_loss\_shares.R

August 16, 2026

## Contents

|                                                   |          |
|---------------------------------------------------|----------|
| compute_sjsdm_decomposition_loss_shares . . . . . | 1        |
| <b>Index</b>                                      | <b>2</b> |

---

|                                             |
|---------------------------------------------|
| compute_sjsdm_decomposition_loss_shares     |
| <i>Compute sjSDM Predictive Loss Shares</i> |

---

## Description

Normalizes positive repeat-level log-loss effects across removed components.

## Usage

```
compute_sjsdm_decomposition_loss_shares(data_repeat_effects = NULL)
```

## Arguments

data\_repeat\_effects  
Repeat table returned by [summarise\_sjsdm\_decomposition\_effects()].

## Details

Negative effects are retained in ‘mean\_delta\_full\_advantage’ but contribute zero to normalized shares. Shares are undefined when no component has a positive effect. These are relative predictive-loss shares, not ecological variance fractions, and component overlap prevents causal interpretation.

## Value

A named list containing repeat-level shares and descriptive share summaries.

## Examples

```
## Not run:  
compute_sjsdm_decomposition_loss_shares(data_repeat_effects)  
  
## End(Not run)
```

# Index

`compute_sjsdm_decomposition_loss_shares,`  
[1](#)