

load_spatial_resolution_prediction_inputs.R

August 16, 2026

Contents

load_spatial_resolution_prediction_inputs 1

Index 3

load_spatial_resolution_prediction_inputs
Read Spatial-Resolution Prediction Inputs

Description

Reads the suffixed targets needed to predict from one ‘pipeline_paleo_spatial_resolution’ model resolution.

Usage

```
load_spatial_resolution_prediction_inputs(  
  store_path,  
  resolution_id = "genus",  
  read_target_fn = targets::tar_read_raw,  
  meta_fn = targets::tar_meta,  
  include_spatial_basis = FALSE  
)
```

Arguments

store_path Character scalar path to a spatial-resolution targets store.

resolution_id Character scalar model resolution identifier, such as “genus”.

read_target_fn Function used to read targets. Defaults to [targets::tar_read_raw()].

meta_fn Function used by [load_targets_store_metadata()] to read metadata.

include_spatial_basis Logical scalar. When ‘TRUE’, append the additive reusable 2-D basis target.
Default is ‘FALSE’ to preserve the existing public return schema.

Value

Named list of model, model input, coordinate, and spatial predictor targets.

Examples

```
## Not run:  
load_spatial_resolution_prediction_inputs(  
  store_path = "Data/targets/paleo_spatial_continental/europe",  
  resolution_id = "genus"  
)  
  
## End(Not run)
```

Index

load_spatial_resolution_prediction_inputs,
[1](#)