

load_targets_target_by_fingerprint.R

August 16, 2026

Contents

load_targets_target_by_fingerprint 1

Index 3

load_targets_target_by_fingerprint
Load a Target Tracked by an External Fingerprint

Description

Loads one target from an external ‘targets’ store while requiring an exact, previously validated fingerprint row for that target. The explicit fingerprint argument creates a local dependency on external scientific content instead of depending only on the store path.

Usage

```
load_targets_target_by_fingerprint(  
  store_path,  
  target_name,  
  data_fingerprint,  
  read_fn = targets::tar_read_raw  
)
```

Arguments

store_path	A single non-empty character string with the targets store path.
target_name	A single non-empty character string naming the target to load.
data_fingerprint	A one-row data frame with columns ‘name’ and ‘data_hash’, as returned by [load_targets_target_fingerprints()].
read_fn	Function used to read the target. Defaults to [targets::tar_read_raw()].

Value

The target value returned by ‘read_fn’.

Examples

```
## Not run:
data_fingerprint <- load_targets_target_fingerprints(
  store_path = "Data/targets/traits_reference/pipeline_traits_reference",
  target_names = "data_traits_classified_corrected"
)
load_targets_target_by_fingerprint(
  store_path = "Data/targets/traits_reference/pipeline_traits_reference",
  target_name = "data_traits_classified_corrected",
  data_fingerprint = data_fingerprint
)

## End(Not run)
```

Index

`load_targets_target_by_fingerprint`, [1](#)