

prepare_coords_for_fit.R

August 16, 2026

Contents

prepare_coords_for_fit	1
Index	2

prepare_coords_for_fit	<i>Prepare Coordinate Data for Model Fitting</i>
------------------------	--

Description

Expands dataset-level coordinate data to the sample level by joining against the canonical '(dataset_name, age)' sample index, producing a data frame whose rows align with the community matrix and abiotic data used for model fitting.

Usage

```
prepare_coords_for_fit(data_coords = NULL, data_sample_ids = NULL)
```

Arguments

data_coords	A data frame with 'dataset_name' as row names and columns 'coord_long' and 'coord_lat'.
data_sample_ids	A data frame of valid '(dataset_name, age)' pairs as returned by 'align_sample_ids()'.

Details

Coordinates are stored at dataset level but models require one row per sample. This function replicates each dataset's coordinates across all its valid sample ages. The row-name format matches that of the community matrix and abiotic data frame produced by the respective preparation functions.

Value

A data frame with row names in the format '"<dataset_name>__<age>"' and columns 'coord_long' and 'coord_lat'. Rows are sorted by 'dataset_name' then 'age', matching the ordering of 'data_sample_ids'.

See Also

[align_sample_ids()], [build_jsdm_fit_input()]

Index

`prepare_coords_for_fit`, [1](#)