

resolve_functional_type_classification_path_from_store.

August 16, 2026

Contents

resolve_functional_type_classification_path_from_store	1
Index	3

resolve_functional_type_classification_path_from_store
<i>Get Functional-Type Classification Path from Store</i>

Description

Resolves the newest functional-type classification ‘.qs’ file for the spatial unit encoded in a ‘targets’ store path.

Usage

```
resolve_functional_type_classification_path_from_store(  
    store = targets::tar_path_store(),  
    path_spatial_grid = here::here("Data/Input/spatial_grid.csv"),  
    path_processed = here::here("Data/Processed/Traits"),  
    data_source_prefix = NULL  
)
```

Arguments

- | | |
|--------------------|--|
| store | A single character string giving the targets store path. Default: ‘targets::tar_path_store()’. |
| path_spatial_grid | Path to the spatial grid CSV catalogue file. Default: ‘here::here("Data/Input/spatial_grid.csv")’. |
| path_processed | A single character string giving the directory that contains dated FT classification ‘.qs’ files. Default: ‘here::here("Data/Processed/Traits")’. |
| data_source_prefix | Optional single non-empty character string identifying a source-specific FT classification family. Use ‘NULL’ (default) for historical paleo/global files, or “modern” for modern files. |

Details

The function extracts 'scale_id' from 'store', resolves the owning 'continent_id' from the spatial grid, finds matching FT classification files in 'path_processed', and returns the most recent file based on the ISO date suffix in the file name. The function errors when 'store' is not a spatial store, when no matching FT classification file exists, or when required inputs are invalid.

Value

A single character string: the path to the newest matching FT classification file for the continent that owns the spatial unit.

See Also

`resolve_scale_id_from_store`, `resolve_continent_ids_from_scale_ids`, `load_latest_functional_type_classification`

Examples

```
resolve_functional_type_classification_path_from_store(  
  store = here::here(  
    "Data/targets/paleo_spatial_regional/eu_r005/",  
    "pipeline_paleo_spatial_resolution"  
  )  
)
```

Index

resolve_functional_type_classification_path_from_store,
[1](#)