

run_sjsdm_prepared_tuning_candidate.R

August 16, 2026

Contents

run_sjsdm_prepared_tuning_candidate	1
Index	3

run_sjsdm_prepared_tuning_candidate
<i>Run One Prepared sjSDM Tuning Candidate</i>

Description

Fits, predicts, and scores one regularization candidate against one previously prepared cross-validation fold.

Usage

```
run_sjsdm_prepared_tuning_candidate(  
  data_candidate = NULL,  
  list_prepared_fold = NULL,  
  list_fold_context = NULL,  
  fit_function = NULL,  
  predict_function = NULL,  
  score_function = score_sjsdm_tuning_predictions,  
  seed = 900723L,  
  epsilon = 1e-06  
)
```

Arguments

data_candidate	One-row candidate table with candidate ID and six regularization values.
list_prepared_fold	Prepared fold containing train input, test input, and observed test data.
list_fold_context	Fold identifiers, sample/location counts, and cross-validation strategy.
fit_function, predict_function, score_function	Injectable fitting, prediction, and scoring functions.
seed	Non-negative base integer used to derive fit and score seeds.
epsilon	Probability clipping tolerance passed to the score function.

Value

Named list containing one-row 'data_tuning' and compact 'list_prediction' output without a fitted model object.

Examples

```
## Not run:
run_sjsdm_prepared_tuning_candidate(
  data_candidate = data_candidate,
  list_prepared_fold = list_prepared_fold,
  list_fold_context = list_fold_context,
  fit_function = fit_sjsdm_model,
  predict_function = predict_sjsdm_model
)

## End(Not run)
```

Index

run_sjsdm_prepared_tuning_candidate, 1