compute_sjsdm_cv_calibration_hashes.R

October 7, 2026

Contents

compute_sjsdm_cv_calibration_hashes 1

Index **3**

`compute_sjsdm_cv_calibration_hashes`
Compute Versioned Scientific Calibration Input Hashes

Description

Hashes analytical input content while retaining raw legacy signatures for verified migrations. Per-fold fingerprints support later recovery audits.

Usage

```
compute_sjsdm_cv_calibration_hashes(
  data_candidates,
  list_prepared_folds,
  sel_abiotic_formula,
  config_sjsdm_cv_fitting,
  repeat_confirmation_loss_tolerance = 0.02
)
```

Arguments

`data_candidates`, `list_prepared_folds`, `sel_abiotic_formula`
: Candidate grid, cached prepared folds and environment formula.

`config_sjsdm_cv_fitting`
: Structural CV fitting configuration with the calibration starting budget.

`repeat_confirmation_loss_tolerance`
: Maximum relative loss gap allowed for repeat-two confirmation.

Value

Current and legacy input hashes and scientific input fingerprints.

Examples

```
## Not run:
compute_sjsdm_cv_calibration_hashes(
  data_candidates, list_prepared_folds, ~ temperature, config_cv
)

## End(Not run)
```

Index

compute_sjsdm_cv_calibration_hashes, 1