

R documentation

of all in
'C:/Users/ondre/AppData/Local/Temp/codex_doc_run_sjsdm_tuning_candidates'
July 1, 2026

Contents

run_sjsdm_tuning_candidates	1
Index	3

run_sjsdm_tuning_candidates
<i>Run sjSDM Tuning Candidates</i>

Description

Fits every deterministic regularization candidate independently on each cross-validation training partition and scores held-out probabilities.

Usage

```
run_sjsdm_tuning_candidates(  
  data_assignments = NULL,  
  data_candidates = NULL,  
  prepare_fold_function = NULL,  
  fit_function = NULL,  
  predict_function = NULL,  
  seed = 900723L,  
  epsilon = 1e-06  
)
```

Arguments

data_assignments
Location-level assignment table with 'repeat_id', 'fold_id', 'location_id', 'n_samples', and 'row_indices'. Optional 'cv_strategy' is propagated.

data_candidates
Candidate table returned by [make_sjsdm_regularization_candidates()].

<code>prepare_fold_function</code>	Injectable function called with <code>'train_indices'</code> , <code>'test_indices'</code> , <code>'repeat_id'</code> , and <code>'fold_id'</code> . It must return <code>'data_train_input'</code> , <code>'data_test_input'</code> , and matrix <code>'data_test_observed'</code> .
<code>fit_function</code>	Injectable function called with <code>'data_train_input'</code> , one-row <code>'candidate'</code> , and deterministic integer <code>'seed'</code> .
<code>predict_function</code>	Injectable function called with fitted <code>'object'</code> and <code>'data_test_input'</code> . It must return a probability matrix aligned to <code>'data_test_observed'</code> .
<code>seed</code>	Single non-negative integer used to derive stable fit seeds. Defaults to <code>'900723L'</code> .
<code>epsilon</code>	Probability clipping tolerance used for held-out log loss. Defaults to <code>'1e-6'</code> .

Details

Fold preparation is run once per repeat and fold. Preparation, fit, prediction, and scoring errors are retained as structured status rows so a failed candidate does not abort the remaining tuning grid.

Value

Compact tibble with one row per repeat, fold, and candidate. It contains candidate parameters, fold counts, total and per-response held-out negative log likelihood, macro AUC, fit status, error text, CV strategy, and regularization source. Fitted objects and prediction matrices are omitted.

Index

run_sjsdm_tuning_candidates, [1](#)