

get_functional_type_classification_path_from_store.R

April 27, 2026

Contents

get_functional_type_classification_path_from_store	1
Index	3

get_functional_type_classification_path_from_store
<i>Get Functional-Type Classification Path from Store</i>

Description

Resolves the newest functional-type classification ‘.qs’ file for the spatial unit encoded in a ‘targets’ store path.

Usage

```
get_functional_type_classification_path_from_store(  
  store = targets::tar_path_store(),  
  path_spatial_grid = here::here("Data/Input/spatial_grid.csv"),  
  path_processed = here::here("Data/Processed/Traits")  
)
```

Arguments

store	A single character string giving the targets store path. Default: ‘targets::tar_path_store()’.
path_spatial_grid	Path to the spatial grid CSV catalogue file. Default: ‘here::here("Data/Input/spatial_grid.csv")’.
path_processed	A single character string giving the directory that contains dated FT classification ‘.qs’ files. Default: ‘here::here("Data/Processed/Traits")’.

Details

The function extracts ‘scale_id’ from ‘store’, resolves the owning ‘continent_id’ from the spatial grid, finds matching FT classification files in ‘path_processed’, and returns the most recent file based on the ISO date suffix in the file name. The function errors when ‘store’ is not a spatial store, when no matching FT classification file exists, or when required inputs are invalid.

Value

A single character string: the path to the newest matching FT classification file for the continent that owns the spatial unit.

See Also

`get_scale_id_from_store`, `get_continent_id_from_scale_id`, `get_functional_type_classification`

Examples

```
get_functional_type_classification_path_from_store(  
  store = here::here(  
    "Data/targets/spatial_regional/eu_r005/",  
    "pipeline_spatial_resolution"  
  )  
)
```

Index

`get_functional_type_classification_path_from_store,`
[1](#)