

make_trait_table.R

April 27, 2026

Contents

make_trait_table 1

Index 3

make_trait_table	<i>Make Wide-Format Species x Traits Table</i>
------------------	--

Description

Pivots a long-format aggregated trait data frame into a wide-format table with one row per taxon and one column per trait domain. This produces the genus x traits matrix used for functional type assignment.

Usage

```
make_trait_table(  
  data,  
  taxon_col = "taxon_name",  
  trait_col = "trait_domain_name",  
  value_col = "trait_value_aggregated"  
)
```

Arguments

data	A data frame in long format with one row per taxon x trait combination. Must contain at least the columns specified by 'taxon_col', 'trait_col', and 'value_col'.
taxon_col	A character string naming the column containing taxon (genus) names. Default: "taxon_name".
trait_col	A character string naming the column containing trait domain names. Default: "trait_domain_name".
value_col	A character string naming the column containing aggregated trait values. Default: "trait_value_aggregated".

Details

Wraps 'tidyr::pivot_wider()'. If a taxon x trait combination appears more than once, only the first value is retained ('values_fn = dplyr::first').

Value

A tibble with one row per taxon and one column per trait domain, plus the taxon name column. Column names for traits are taken directly from the values in 'trait_col'.

See Also

[aggregate_trait_values()], [check_trait_coverage()]

Index

`make_trait_table`, [1](#)