

# aggregate\_sjsdm\_tuning\_by\_tier.R

September 10, 2026

## Contents

|                                          |          |
|------------------------------------------|----------|
| aggregate_sjsdm_tuning_by_tier . . . . . | 1        |
| <b>Index</b>                             | <b>3</b> |

---

|                                       |
|---------------------------------------|
| aggregate_sjsdm_tuning_by_tier        |
| <i>Aggregate sjSDM Tuning by Tier</i> |

---

## Description

Aggregates normalized candidate loss within source IDs and then across a compatible spatial tier using equal source-ID weighting.

## Usage

```
aggregate_sjsdm_tuning_by_tier(  
  data_tuning_summary = NULL,  
  include_sample_weighted = TRUE  
)
```

## Arguments

|                         |                                                                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| data_tuning_summary     | Repeat-level tuning summaries from [summarise_sjsdm_tuning_candidates()] with source and model-context columns.                                   |
| include_sample_weighted | Logical scalar. When true, also reports a sensitivity selection weighted by the number of observed response values contributed by each source ID. |

## Details

Input rows must describe one tier, taxonomic resolution, response family, predictor structure, and candidate-table hash. Every source ID must provide the same candidate identifiers and parameter values. Candidates with an incomplete result for any source ID remain visible but are not selectable.

**Value**

Named list with `source_candidate_loss`, `candidate_aggregation`, and `selection_sensitivity` tibbles. The primary selection always uses equal source-ID weighting.

**Examples**

```
## Not run:  
aggregate_sjsdm_tuning_by_tier(  
  data_tuning_summary = data_tuning_summary  
)  
  
## End(Not run)
```

# Index

`aggregate_sjsdm_tuning_by_tier`, [1](#)