

build_community_interpolation_index.R

September 10, 2026

Contents

build_community_interpolation_index 1

Index 3

build_community_interpolation_index
Build Community Interpolation Index

Description

Builds small per-dataset row-range metadata for paleo interpolation.

Usage

```
build_community_interpolation_index(  
  data_community = NULL,  
  data_age_uncertainty = NULL  
)
```

Arguments

`data_community` A data frame containing a 'dataset_name' column. Rows for each dataset must be contiguous.

`data_age_uncertainty` A data frame containing a 'dataset_name' column. Rows for each dataset must be contiguous. Datasets without uncertainty rows are supported.

Details

Dynamic 'targets' branches receive constant-size row ranges instead of nested data frames. This avoids scanning the complete shared inputs and allocating a full-table logical mask in every worker branch.

Value

A list of branch metadata objects. Each object contains 'dataset_name', 'flag_empty', and inclusive row ranges for both shared input tables.

See Also

[[interpolate_community_dataset_from_shared_inputs\(\)](#)]

Examples

```
data_community <-  
  tibble::tibble(  
    dataset_name = base::c("core_b", "core_a")  
  )  
data_age_uncertainty <-  
  tibble::tibble(  
    dataset_name = "core_a"  
  )  
  
build_community_interpolation_index(  
  data_community = data_community,  
  data_age_uncertainty = data_age_uncertainty  
)
```

Index

`build_community_interpolation_index`, [1](#)