

build_sjsdm_regularization_candidates.R

September 10, 2026

Contents

build_sjsdm_regularization_candidates 1

Index 3

build_sjsdm_regularization_candidates
Make sjSDM Regularization Candidates

Description

Builds a deterministic Cartesian product of configured sjSDM alpha and lambda values for project-owned cross-validation tuning.

Usage

```
build_sjsdm_regularization_candidates(  
  alpha_cov = 0.5,  
  alpha_coef = 0.5,  
  alpha_spatial = 0.5,  
  lambda_cov = 0,  
  lambda_coef = 0,  
  lambda_spatial = 0  
)
```

Arguments

alpha_cov, alpha_coef, alpha_spatial
Non-empty numeric vectors of unique finite alpha values between zero and one, inclusive.

lambda_cov, lambda_coef, lambda_spatial
Non-empty numeric vectors of unique finite non-negative lambda values.

Details

Input order does not affect the returned table. The same configured value sets therefore produce the same candidate IDs in every fold and repeat.

Value

Tibble with one row per unique candidate. Columns are 'candidate_id', the three alpha values, and the three lambda values. Rows are sorted by the six parameter values and IDs use deterministic zero-padded sequence numbers.

Examples

```
build_sjsdm_regularization_candidates(  
  alpha_cov = c(0, 0.5),  
  lambda_cov = c(0, 0.1)  
)
```

Index

build_sjsdm_regularization_candidates,
[1](#)