

# build\_sjsdm\_tuning\_schedule.R

September 10, 2026

## Contents

|                                       |          |
|---------------------------------------|----------|
| build_sjsdm_tuning_schedule . . . . . | 1        |
| <b>Index</b>                          | <b>3</b> |

---

|                                       |
|---------------------------------------|
| build_sjsdm_tuning_schedule           |
| <i>Build an sjSDM Tuning Schedule</i> |

---

## Description

Validates exhaustive or staged cross-validation tuning settings and builds the deterministic repeat-level candidate budget used by every model pipeline.

## Usage

```
build_sjsdm_tuning_schedule(  
  tuning_strategy = NULL,  
  n_candidates = NULL,  
  repeat_ids = NULL,  
  survivor_counts = NULL  
)
```

## Arguments

|                 |                                                                                           |
|-----------------|-------------------------------------------------------------------------------------------|
| tuning_strategy | Character scalar. Either "exhaustive" or "staged".                                        |
| n_candidates    | Positive integer number of regularization candidates.                                     |
| repeat_ids      | Unique positive integer repeat identifiers in execution order.                            |
| survivor_counts | Integer counts retained after each non-final staged round. Ignored for exhaustive tuning. |

## Value

Tibble with one row per tuning round and columns 'tuning\_strategy', 'strategy\_version', 'round\_id', 'repeat\_id', 'n\_candidates\_entering', and 'n\_candidates\_surviving'.

**Examples**

```
build_sjsdm_tuning_schedule(  
  tuning_strategy = "staged",  
  n_candidates = 8L,  
  repeat_ids = 1:3,  
  survivor_counts = c(4L, 2L)  
)
```

# Index

`build_sjsdm_tuning_schedule`, [1](#)