

build_trait_review_candidates.R

September 10, 2026

Contents

build_trait_review_candidates	1
---	---

Index	3
--------------	----------

build_trait_review_candidates	
<i>Build Trait Review Candidates</i>	

Description

Builds an auditable taxon-by-domain review queue from within-taxon trait outlier flags, objective invalid values, and optional source review keys. Domain-level flags remain diagnostic and do not create candidates alone.

Usage

```
build_trait_review_candidates(  
  data_trait_records,  
  data_source_candidates = NULL,  
  review_stage = "raw",  
  domain_iqr_multiplier = 3,  
  taxon_iqr_multiplier = 1.5,  
  minimum_taxon_records = 10L  
)
```

Arguments

data_trait_records	Trait records containing 'taxon_name', 'trait_domain_name', and 'trait_value'.
data_source_candidates	Optional data frame containing 'taxon_name', 'trait_domain_name', and 'source_reference' from an external review source.
review_stage	Character scalar: either "raw" or "classified".
domain_iqr_multiplier	Positive numeric domain-level IQR multiplier. Default: '3'.

`taxon_iqr_multiplier`

Positive numeric within-taxon IQR multiplier. Default: '1.5'.

`minimum_taxon_records`

Positive integer minimum group size. Default: '10L'.

Value

A tibble with one row per review candidate and a stable SHA-256 'candidate_id'.

Index

`build_trait_review_candidates`, [1](#)