

compute_sjsdm_decomposition_fold_effects.R

September 10, 2026

Contents

compute_sjsdm_decomposition_fold_effects	1
Index	3

compute_sjsdm_decomposition_fold_effects
<i>Compare Matched-Fold sjSDM Decomposition Metrics</i>

Description

Pairs full and reduced sjSDM metrics by repeat, fold, taxon, and metric, retaining raw component-removal effects and explicit evaluability statuses.

Usage

```
compute_sjsdm_decomposition_fold_effects(  
  data_fold_metrics = NULL,  
  data_taxon_eligibility = NULL  
)
```

Arguments

data_fold_metrics	Long-format metric table containing full and reduced model variants.
data_taxon_eligibility	Taxon table containing unique ‘taxon’ and logical ‘eligible’ columns.

Details

For Tjur R2 and AUC, the effect is full minus reduced. For log loss and Brier score, the effect is reduced minus full. Negative effects are retained.

Value

A tibble with one row per reduced variant, repeat, fold, taxon, and metric. ‘delta_full_advantage’ is positive when the full model performs better.

Examples

```
## Not run:
compute_sjsdm_decomposition_fold_effects(
  data_fold_metrics = data_metrics,
  data_taxon_eligibility = data_eligibility
)

## End(Not run)
```

Index

`compute_sjsdm_decomposition_fold_effects,`
[1](#)