

diagnose_trait_matrix_readiness.R

September 10, 2026

Contents

diagnose_trait_matrix_readiness	1
Index	3

diagnose_trait_matrix_readiness
<i>Diagnose Trait Matrix Readiness</i>

Description

Summarises coverage, transformed dynamic range, invalid values, and robust taxon-level extremes in a community trait matrix without changing values.

Usage

```
diagnose_trait_matrix_readiness(  
  data_trait_table,  
  vec_trait_transformations,  
  taxon_column = "taxon_name",  
  maximum_missing_fraction = 0.5,  
  maximum_transformed_range = 4,  
  outlier_fence_multiplier = 3  
)
```

Arguments

- data_trait_table
Wide taxon-by-trait data frame.
- vec_trait_transformations
Named transformation contract accepted by [prepare_trait_matrix_for_dissimilarity()].
- taxon_column
Character scalar naming the taxon identifier column.
- maximum_missing_fraction
Maximum acceptable missing fraction per trait domain.
- maximum_transformed_range
Maximum acceptable transformed range.
- outlier_fence_multiplier
Non-negative Tukey-fence multiplier.

Value

A named list containing 'data_domain_summary', 'data_taxon_anomalies', and scalar 'flag_ready'.

Examples

```
diagnose_trait_matrix_readiness(  
  data_trait_table = tibble::tibble(  
    taxon_name = c("A", "B"),  
    `Plant heigh` = c(10, 100)  
  ),  
  vec_trait_transformations = c(`Plant heigh` = "log10")  
)
```

Index

diagnose_trait_matrix_readiness, [1](#)