

diagnose_trait_source_anomalies.R

September 10, 2026

Contents

diagnose_trait_source_anomalies	1
Index	3

diagnose_trait_source_anomalies
<i>Diagnose Trait Source Anomalies</i>

Description

Prioritises multiplicative source-taxon unit anomalies using positive trait medians, independent-source agreement, and robust domain-level log ranges. The findings are diagnostic and never modify or approve corrections.

Usage

```
diagnose_trait_source_anomalies(  
  data_trait_records,  
  source_factor_relative_tolerance = 0.25,  
  minimum_log10_gap = 0.75,  
  outlier_fence_multiplier = 3  
)
```

Arguments

- data_trait_records
Long trait records retaining taxon, source, domain, and value columns.
- source_factor_relative_tolerance
Maximum relative distance from the nearest power-of-ten factor.
- minimum_log10_gap
Minimum absolute source comparison gap.
- outlier_fence_multiplier
Non-negative domain log-IQR multiplier.

Value

A named list containing ‘data_source_taxon_summary’, ‘data_source_anomalies’, and ‘data_domain_summary’.

Examples

```
diagnose_trait_source_anomalies(  
  tibble::tibble(  
    taxon_name = c("A", "A"),  
    data_source_id = c(1L, 2L),  
    trait_domain_name = "Stem specific density",  
    trait_value = c(0.0003, 0.3)  
  )  
)
```

Index

diagnose_trait_source_anomalies, [1](#)