

evaluate_sjsdm_taxon_eligibility.R

September 10, 2026

Contents

evaluate_sjsdm_taxon_eligibility	1
Index	3

evaluate_sjsdm_taxon_eligibility
<i>Assess sjSDM Taxon Eligibility</i>

Description

Applies prespecified prevalence and fold-evaluability rules to fold-local sjSDM metrics.

Usage

```
evaluate_sjsdm_taxon_eligibility(  
  data_fold_metrics = NULL,  
  minimum_prevalence = 0.05,  
  maximum_prevalence = 0.95,  
  minimum_evaluable_fraction = 0.8  
)
```

Arguments

data_fold_metrics	Fold-local metric table returned by [evaluate_sjsdm_fold_predictions()].
minimum_prevalence	Minimum observation-weighted prevalence. Defaults to ‘0.05’.
maximum_prevalence	Maximum observation-weighted prevalence. Defaults to ‘0.95’.
minimum_evaluable_fraction	Minimum fraction of folds with an evaluable model Tjur R2. Defaults to ‘0.8’.

Details

Eligibility is based only on model Tjur R2 rows. Prevalence is calculated from summed held-out presences and observations so unequal folds are weighted by their observation counts.

Value

One-row-per-taxon tibble with prevalence, fold coverage, mean evaluable Tjur R2, component checks, overall eligibility, and a deterministic status.

Examples

```
## Not run:  
evaluate_sjsdm_taxon_eligibility(data_fold_metrics = data_metrics)  
  
## End(Not run)
```

Index

`evaluate_sjsdm_taxon_eligibility`, [1](#)