

extract_jsdm_variance_fractions.R

September 10, 2026

Contents

extract_jsdm_variance_fractions 1

Index 3

extract_jsdm_variance_fractions
Extract Variance Fractions from a Single sjSDM Object

Description

Extracts specified variance partitioning fractions from a single sjSDManova object, returning a two-column tibble with fraction labels and their Nagelkerke RB2 values.

Usage

```
extract_jsdm_variance_fractions(  
  anova_object,  
  vec_anova_fractions = base::c("F_A", "F_B", "F_S", "F_AB", "F_AS", "F_BS", "F_ABS"),  
  clamp_negative = TRUE  
)
```

Arguments

anova_object A single sjSDManova-like list containing a named "results" element with columns 'models' and "R2 Nagelkerke".

vec_anova_fractions A non-empty character vector of fraction codes to retain (e.g. 'c("F_A", "F_B", "F_S")').

clamp_negative A single logical (default 'TRUE'). If 'TRUE', negative Nagelkerke RB2 values are clamped to 0.

Details

Accesses the named "results" element with 'purrr::chuck()', filters the requested fraction codes, and translates them to human-readable component labels.

Value

A tibble with columns:

component Character. Human-readable component label (e.g. "Abiotic", "Associations", "Spatial").

R2_Nagelkerke Numeric. Nagelkerke RB2 value for each fraction, optionally clamped to [0, Inf).

See Also

[[aggregate_jsdm_variance_components\(\)](#)]

Index

`extract_jsdm_variance_fractions`, [1](#)