

filter_community_by_minimum_core_count.R

September 10, 2026

Contents

filter_community_by_minimum_core_count	1
Index	3

filter_community_by_minimum_core_count
<i>Filter Community by Minimum Core Count</i>

Description

Filters out taxa that are not present in a sufficient number of cores (distinct datasets). Only taxa occurring in at least 'minimum_core_count' distinct 'dataset_name' values are retained. This removes taxa that appear in only a single core, which can disproportionately influence the species-species co-occurrence matrix.

Usage

```
filter_community_by_minimum_core_count(  
  data_community = NULL,  
  minimum_core_count = 2  
)
```

Arguments

data_community	A data frame containing community data in long format. Must include columns 'taxon' and 'dataset_name'.
minimum_core_count	A single positive integer specifying the minimum number of distinct cores (datasets) a taxon must appear in to be retained. Default is 2.

Details

The function counts distinct 'dataset_name' values per 'taxon' across the entire dataset. Taxa with fewer cores than 'minimum_core_count' are removed. An error is raised if no taxa remain after filtering, which may indicate that 'minimum_core_count' is set too high.

Value

A filtered data frame containing only taxa that appear in at least ‘minimum_core_count’ distinct datasets. All original columns are preserved.

See Also

[filter_community_by_minimum_sample_count()], [filter_community_by_minimum_proportion()],
[select_top_taxa_by_group_occurrence()]

Index

`filter_community_by_minimum_core_count,`
[1](#)