

interpolate_community_dataset_from_shared_inputs.R

September 10, 2026

Contents

interpolate_community_dataset_from_shared_inputs	1
Index	3

interpolate_community_dataset_from_shared_inputs
<i>Interpolate Community Dataset from Shared Inputs</i>

Description

Slices shared paleo preprocessing inputs to one dataset and interpolates it.

Usage

```
interpolate_community_dataset_from_shared_inputs(  
  list_interpolation_index = NULL,  
  data_community = NULL,  
  data_age_uncertainty = NULL,  
  n_cores = 1L,  
  ...  
)
```

Arguments

list_interpolation_index	A metadata object produced by [build_community_interpolation_index()].
data_community	Community data or a descriptor from [build_shared_interpolation_data()].
data_age_uncertainty	Age-uncertainty data or a shared descriptor.
n_cores	Number of cores passed to [interpolate_paleo_community_with_age_uncertainty()]. Dynamic target branches should use '1L'.
...	Additional arguments passed to [interpolate_paleo_community_with_age_uncertainty()].

Details

Inclusive row ranges keep branch payloads constant in size and avoid full-table logical masks inside concurrent workers. During the one-time migration from persisted live ‘mori’ handles, a prebuild may reuse an existing branch object after separately confirming durable inputs are current.

Value

A data frame with columns ‘dataset_name’, ‘taxon’, ‘age’, and ‘value’.

See Also

[[build_community_interpolation_index\(\)](#)], [[interpolate_paleo_community_with_age_uncertainty\(\)](#)]

Index

`interpolate_community_dataset_from_shared_inputs,`
[1](#)