

load_config_value_with_fallback.R

September 10, 2026

Contents

load_config_value_with_fallback	1
Index	3

load_config_value_with_fallback	
<i>Load Configuration Value with Fallback</i>	

Description

Retrieves a configuration value from the active configuration. If the key is absent there, the function falls back to the same key in a named fallback configuration.

Usage

```
load_config_value_with_fallback(  
  config_section,  
  config_key,  
  fallback_config = "default",  
  file = here::here("config.yml")  
)
```

Arguments

config_section	A single character string naming the configuration section to read, such as "data_processing".
config_key	A single character string naming the configuration setting within 'config_section'.
fallback_config	A single character string naming the configuration to use when the active configuration does not define 'config_key'.
file	Path to the YAML configuration file. Defaults to 'here::here("config.yml")'.

Details

The function is intended for pipelines that keep a shared set of defaults in a dedicated configuration while still allowing project-specific overrides in the active configuration. If 'R_CONFIG_ACTIVE' is unset, the helper reads from "default". Both the active config name and 'fallback_config' must exist in the YAML file.

Value

A scalar configuration value read from the active configuration or from ‘fallback_config’ when the active configuration does not define ‘config_key’.

See Also

[load_active_config_value()], [load_config_value()]

Examples

```
load_config_value_with_fallback(  
    config_section = "data_processing",  
    config_key = "min_n_samples"  
)  
load_config_value_with_fallback(  
    config_section = "data_processing",  
    config_key = "ft_groups_min",  
    fallback_config = "project_traits_reference"  
)
```

Index

`load_config_value_with_fallback`, [1](#)