

load_model_tuning_parameter_for_scale_and_resolution

September 10, 2026

Contents

load_model_tuning_parameter_for_scale_and_resolution	1
Index	3

load_model_tuning_parameter_for_scale_and_resolution
<i>Get One Model Tuning Parameter For Scale And Resolution</i>

Description

Returns one active model-fitting tuning parameter. Spatial stores read per-scale tuning from the model tuning CSV files; non-spatial stores fall back to scalar values from ‘config.yml’.

Usage

```
load_model_tuning_parameter_for_scale_and_resolution(  
  param_id,  
  scale_id = resolve_scale_id_from_store(),  
  resolution_id = NULL,  
  config_file = here::here("config.yml"),  
  dir = here::here("Data/Input/Model_tuning")  
)
```

Arguments

param_id	A single model tuning parameter name. Must be one of ‘n_iter’, ‘n_step_size’, ‘n_sampling’, ‘n_samples_anova’, or ‘n_early_stopping’.
scale_id	Optional spatial unit identifier. Defaults to ‘resolve_scale_id_from_store()’. When ‘NULL’, values are read from ‘config.yml’.
resolution_id	Optional model resolution. Defaults to the active ‘data_processing\$taxonomic_resolution’ config value. Spatial stores pass this to ‘load_model_tuning_parameters()’.
config_file	Path to the YAML configuration file. Default: ‘here::here("config.yml”)’.
dir	Directory containing model tuning CSV files. Default: ‘here::here("Data/Input/Model_tuning”)’.

Value

The requested parameter value. Optional tuning parameters may return 'NULL'.

See Also

`load_model_tuning_parameters`

Index

`load_model_tuning_parameter_for_scale_and_resolution,`
[1](#)