

resolve_cross_validation_strategy.R

September 10, 2026

Contents

resolve_cross_validation_strategy	1
Index	3

resolve_cross_validation_strategy
<i>Assess Cross-Validation Feasibility</i>

Description

Evaluates full-model and candidate training-partition diagnostics and selects the first viable cross-validation strategy.

Usage

```
resolve_cross_validation_strategy(  
  data_partition_diagnostics = NULL,  
  min_train_locations = NULL,  
  min_train_samples = NULL,  
  min_train_taxa = NULL,  
  min_mem_locations = NULL  
)
```

Arguments

data_partition_diagnostics	Data frame with one row for the full model and one row per candidate training partition. Required columns are 'cv_strategy', 'repeat_id', 'effective_folds', 'fold_id', 'n_train_locations', 'n_train_samples', 'n_train_taxa', and 'n_train_mem_locations'. Supported strategies are "full_model", "spatially_stratified_group_kfold", and "leave_one_location_out".
min_train_locations, min_train_samples, min_train_taxa	Positive integer thresholds required in the full model and every selected training partition.
min_mem_locations	Positive integer minimum number of locations required for MEM construction.

Details

The full model is checked first. Viable grouped candidates are preferred in ascending fold-count order, followed by leave-one-location-out. A viable full model without any viable holdout requires tier-pooled regularization.

Value

One-row tibble containing full-data counts, feasibility flags, selected 'cv_strategy', 'effective_folds', and 'cv_feasibility_status'.

Examples

```
data_diagnostics <-  
  tibble::tibble(  
    cv_strategy = "full_model",  
    repeat_id = 0L,  
    effective_folds = NA_integer_,  
    fold_id = 0L,  
    n_train_locations = 7L,  
    n_train_samples = 70L,  
    n_train_taxa = 10L,  
    n_train_mem_locations = 7L  
  )  
resolve_cross_validation_strategy(  
  data_partition_diagnostics = data_diagnostics,  
  min_train_locations = 5L,  
  min_train_samples = 5L,  
  min_train_taxa = 3L,  
  min_mem_locations = 4L  
)
```

Index

`resolve_cross_validation_strategy`, [1](#)