

resolve_preprocessing_worker_count.R

September 10, 2026

Contents

resolve_preprocessing_worker_count 1

Index 3

resolve_preprocessing_worker_count
Resolve the Preprocessing Worker Count

Description

Resolves a safe interpolation worker count from configured workers, a resource profile, an explicit override, and currently available memory.

Usage

```
resolve_preprocessing_worker_count(  
  configured_workers = NULL,  
  resource_profile = "shared",  
  workers_override = NULL,  
  available_memory_bytes = NULL  
)
```

Arguments

`configured_workers`
Positive integer worker count from the active analysis profile.

`resource_profile`
One of 'shared', 'dedicated', or 'configured'.

`workers_override`
Optional explicit positive integer override. A non-empty value has highest priority.

`available_memory_bytes`
Optional available-memory estimate in bytes. 'NULL' queries 'ps' when it is available and otherwise skips the memory cap.

Details

The shared and dedicated profiles cap concurrency at four and eight workers, respectively. The configured profile preserves the analysis configuration. A conservative memory admission rule reserves eight GiB and allows at most one worker per four remaining GiB. The explicit override bypasses profile caps but not the memory admission rule.

Value

A single positive integer worker count.

Index

`resolve_preprocessing_worker_count`, [1](#)