

resolve_trait_taxon_ids.R

September 10, 2026

Contents

resolve_trait_taxon_ids	1
Index	3

resolve_trait_taxon_ids

Resolve Trait Taxon IDs to Taxon Names

Description

Replaces numeric 'taxon_id' values in a cleaned trait data frame with the corresponding 'taxon_name' from the 'Taxa' table in the VegVault SQLite database. Rows with unresolved IDs receive 'NA' for 'taxon_name' (standard left-join behaviour).

Usage

```
resolve_trait_taxon_ids(  
  data_trait_records,  
  path_vegvault = here::here("Data/Input/VegVault.sqlite")  
)
```

Arguments

`data_trait_records` A data frame with at least the column 'taxon_id' (integer or numeric), typically the output of `[filter_complete_trait_records()]`.

`path_vegvault` A single character string giving the path to the VegVault SQLite database (default: `'here::here("Data/Input/VegVault.sqlite")'`).

Details

Opens a fresh database connection, loads the 'Taxa' table, filters it to only the IDs present in 'data_trait_records', performs a left join, and closes the connection via `'on.exit()'`.

Value

A tibble with 'taxon_name', all source identifiers, and the trait fields. The original 'taxon_id' is retained for auditability.

See Also

[[filter_complete_trait_records\(\)](#)], [[load_continental_trait_records_from_vegvault\(\)](#)]

Index

`resolve_trait_taxon_ids`, [1](#)