

run_sjsdm_common_regularization_sensitivity.R

September 10, 2026

Contents

run_sjsdm_common_regularization_sensitivity	1
Index	3

run_sjsdm_common_regularization_sensitivity
<i>Run Common-Regularization sjSDM Sensitivity Models</i>

Description

Reads prepared representative-model inputs, refits each model with a common spatial regularization artifact, and returns decomposition and provenance.

Usage

```
run_sjsdm_common_regularization_sensitivity(  
  data_model_index = NULL,  
  data_artifacts = NULL,  
  read_target_function = targets::tar_read_raw,  
  fit_function = NULL,  
  standard_error_function = compute_jsdm_se,  
  anova_function = compute_jsdm_variance_partition,  
  extract_function = extract_jsdm_variance_fractions  
)
```

Arguments

data_model_index	Model index with model_id, tier_id, scale_id, resolution_id, and store_path.
data_artifacts	Common artifacts from [build_sjsdm_common_regularization_artifacts()].
read_target_function	Injectable target reader. Defaults to [targets::tar_read_raw()].
fit_function	Injectable high-level model-fitting function. It receives prepared input, formula, fitting configuration, and one regularization artifact.

`standard_error_function`

Injectable standard-error function. Defaults to `[compute_jsdm_se()]`.

`anova_function` Injectable decomposition function. Defaults to `[compute_jsdm_variance_partition()]`.

`extract_function`

Injectable ANOVA extractor. Defaults to `[extract_jsdm_variance_fractions()]`.

Value

Named list containing fitted models, ANOVA objects, model-level provenance, and a long decomposition table. Individual failures are retained with an explicit status and do not discard successful representative models.

Index

run_sjsdm_common_regularization_sensitivity,
[1](#)