

run_sjsdm_cross_tier_sensitivity.R

September 10, 2026

Contents

run_sjsdm_cross_tier_sensitivity 1

Index 3

run_sjsdm_cross_tier_sensitivity
Run Common sjSDM Sensitivity When Stores Are Ready

Description

Checks every enabled tier's configured representative model store before running the cross-tier common-regularization sensitivity pipeline.

Usage

```
run_sjsdm_cross_tier_sensitivity(  
  profile_ids = NULL,  
  pipeline_name = NULL,  
  sensitivity_script = base::file.path("R", "Pipelines",  
    "pipeline_sjsdm_common_regularization_sensitivity.R"),  
  config_file = here::here("config.yml"),  
  project_root = here::here(),  
  config_load_function = load_config,  
  dir_exists_function = fs::dir_exists,  
  run_pipeline_function = run_pipeline  
)
```

Arguments

profile_ids	Non-empty character vector of unique spatial configuration profile IDs.
pipeline_name	Single spatial-resolution pipeline directory name.
sensitivity_script	Common-regularization sensitivity pipeline script path.
config_file	Configuration file passed to 'config_load_function'.
project_root	Project root used to resolve configured relative target-store paths.

`config_load_function`
 Injectable complete-configuration loader. Defaults to `[load_config()]`.

`dir_exists_function`
 Injectable directory-existence predicate. Defaults to `[fs::dir_exists()]`.

`run_pipeline_function`
 Injectable pipeline runner. Defaults to `[run_pipeline()]`.

Details

The sensitivity pipeline is an all-tier operation. It is not started unless every configured representative store exists, so a standalone local runner can finish without failing on absent continental or regional stores.

Value

Tibble with one row per requested profile, its representative store status, and a sensitivity status of `"completed"`, `"skipped_missing_store"`, or `"skipped_disabled"`.

Examples

```
## Not run:
run_sjsdm_cross_tier_sensitivity(
  profile_ids = c(
    "project_paleo_spatial_continental",
    "project_paleo_spatial_regional",
    "project_paleo_spatial_local"
  ),
  pipeline_name = "pipeline_paleo_spatial_resolution"
)

## End(Not run)
```

Index

`run_sjsdm_cross_tier_sensitivity`, [1](#)