

run_sjsdm_cv_preparation_sequence.R

September 10, 2026

Contents

run_sjsdm_cv_preparation_sequence 1

Index 3

run_sjsdm_cv_preparation_sequence

Run the sjSDM Cross-Validation Preparation Sequence

Description

Builds selected cross-validation preparation targets in isolated unit stores without requesting tuning fits or final models.

Usage

```
run_sjsdm_cv_preparation_sequence(  
  unit_pipeline = NULL,  
  preparation_target_names = NULL,  
  unit_store_suffixes = NULL,  
  prebuild_interpolation = FALSE,  
  preparation_resource_profile = "shared",  
  interpolation_workers_override = NULL,  
  run_pipeline_function = run_pipeline,  
  target_store = load_active_config_value("target_store"),  
  resolve_store_function = resolve_pipeline_store_path,  
  load_metadata_function = load_targets_store_metadata,  
  classify_error_function = classify_sjsdm_unit_pipeline_error,  
  diagnose_endpoints_function = diagnose_sjsdm_cv_preparation_endpoints,  
  read_target_function = targets::tar_read_raw,  
  invalidate_target_function = targets::tar_invalidate,  
  validate_endpoints = base::identical(run_pipeline_function, run_pipeline),  
  cache_recovery_attempts = 8L  
)
```

Arguments

`unit_pipeline` Character scalar path to the production unit pipeline.

`preparation_target_names`
Non-empty character vector of prepared-fold target names.

`unit_store_suffixes`
Optional character vector of spatial-unit store suffixes. 'NULL' runs the non-nested store used by a temporal profile.

`prebuild_interpolation`
Logical forwarded to `[run_pipeline()]` for each unit execution.

`preparation_resource_profile`
Runtime resource profile forwarded to `[run_pipeline()]`.

`interpolation_workers_override`
Optional explicit positive interpolation worker count.

`run_pipeline_function`
Injectable pipeline runner. Defaults to `[run_pipeline()]`.

`target_store` Root target-store path used to inspect unit-level target errors.

`resolve_store_function`
Injectable unit-store path resolver.

`load_metadata_function, classify_error_function`
Injectable target-metadata loader and unit-error classifier.

`diagnose_endpoints_function`
Injectable prepared-endpoint diagnostic.

`read_target_function`
Injectable raw target reader used by endpoint validation.

`invalidate_target_function`
Injectable target invalidator used for legacy-cache recovery.

`validate_endpoints`
Logical. If 'TRUE', require every requested endpoint to have successful, hashed metadata and to be readable. Defaults to 'TRUE' for the production pipeline runner and 'FALSE' for injected test runners.

`cache_recovery_attempts`
Non-negative integer maximum number of targeted legacy-cache retries.

Details

This function is used only when a main-analysis runner is explicitly placed in CV-fold preparation mode. A target-level failure in one spatial unit or temporal store is recorded so all remaining independent work can be attempted. Expected infeasibility is accepted. Unexplained target failures and per-unit runner failures without fresh target metadata are reported after all spatial units have been attempted. This guarantees maximum unit coverage while keeping unexpected outcomes visible at component exit. Legacy-cache recovery follows all affected targets and dependencies visible in metadata, but stops for registered data limitations or when an invalidation makes no progress. Final unexplained-error output is grouped once per unit.

Value

Invisibly, a unit-status tibble. Prepared targets remain cached in production stores.

Index

run_sjsdm_cv_preparation_sequence, [1](#)